

Apex Series LED Cylinder

Surface, Cord, Stem, Wall Mount



Project:	Type:
Product Code:	Date:

Spec Sheet V-12.01.19



Large, white, cord mount shown

- Apex Series DCCX delivers vivid, accurate light in the form of a completely customizable cylinder
- Powered by the high-performance DRD2X module for a precise, targeted beam of low glare illumination
- Produces up to 4,000 candelas of focused light, perfect for unfinished and high ceilings
- Range of form factors and options to adapt to all kinds of applications

Lumen Output 600 lm (10.0W), 750 lm (12.5W)	Mount Surface, Stem, Cord, Wall, Wall Up/Down	
Color Quality 90+ CRI, 2-step SDCM	Size Length: Small (4"), Medium (8"), Large (12") Diameter: 4"	
Color Temperature  2700K 3000K 3500K 4000K	Finish White, Black, Brushed Aluminum, Bronze, Custom	
Optics  Spot (20°) Narrow Flood (30°) Flood (40°)	Stem/Cord Length 24" (standard), Up to 96" (custom)	Input Voltage 120/277V
	Dimming TRIAC/ELV 5% 0-10V 1% Lutron Hi-lume® 1%	
Center Beam Candlepower (CBCP) 4000cd (Spot, 750 lm)	Emergency Lighting Optional Emergency Inverter or LED Driver for lighting up to 90 minutes in event of power failure	

Standards



Ratings



Wet location available

Guarantee

50,000 hrs | 5 years

**PRODUCT BUILDER****CYLINDER**

PRODUCT CODE		MOUNT & CYLINDER		SIZE		LUMENS		CCT		OPTICS		FINISH		DRIVER	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DCCX	Cylinder	SW	Surface Mount, Wet	S	Small	06	600 lm	27	2700K	S	Spot	W	White	[Blank]	TRIAC/ELV
		CM	Cord Mount ^{1,2}	M	Medium	07	750 lm	30	3000K	N	Narrow Flood	B	Black	O	0-10V ³
		TM	Stem Mount ¹	L	Large	66	600 lm up/down ⁴	35	3500K	F	Flood	Z	Bronze	C	Lutron LDE1 ^{3,5}
		TW	Stem Mount, Wet ¹			77	750 lm up/down ⁴	40	4000K	X	Spot, Narrow ⁴	A	Brushed Aluminum	L	Lutron LTEA2W ^{3,6}
		WM	Wall Mount ³							Y	Spot, Flood ⁴	C	Custom Color	TE	TRIAC/ELV, Remote Inverter
		WW	Wall Mount, Wet ³							Z	Narrow, Flood ⁴			OE	0-10V, EM Driver ³
														CE	Lutron LDE1, EM Driver ^{3,5}
														LE	Lutron LTEA2W, EM Driver ^{3,6}

ACCESSORIES

<input type="text"/>	
DCC2X-CCM	Custom Length Cord Mount (up to 96") ¹
DCC2X-CTM	Custom Length Stem Mount (up to 96") ¹
DCC2X-48CM	48" Alternate Length Cord Mount ¹
DCC2X-DFT	Decorative Frosted Trim

¹ 24" standard length, 48" no charge alternate length (cord); Use Custom Order Form to specify custom length² White cord standard for White finish, black cord standard for Black or Bronze finish, silver cord standard for Brushed Aluminum finish; unless specified otherwise³ Only available in Medium or Large size⁴ Only applicable for Large Wall Mounts⁵ Lutron LDE1 Dimming refers to Lutron Hi-lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black⁶ Lutron LTEA2W Dimming refers to Lutron Hi-lume 1% 2-wire LED driver, 120V only